

## ClearSec GD

### GD Range – Internal/External Full Height Security Turnstile

<b>Rotor Elements:</b>	GD90 4N <sup>o</sup> GD120 3N <sup>o</sup>
<b>Drive:</b>	Hand operated
<b>Orientation:</b>	Pass Left or Pass Right
<b>Materials:</b>	Turnstile Casework: 304 Grade Grained Stainless Steel (EN10088-2 Grade 1G/2G) Infills: 6.4mm Thick Laminated Glass Panels Turnstile Roof: 304 Grade Grained Stainless Steel (EN10088-2 Grade 1G/2G) Rotor Arms: 316 Grade Satin Polished Stainless Steel EN10088-2 Grade 1K/2K) Rotor Column: 100mm dia Mild Steel Painted Black Polyester Powder Coated



**Function:** Passage in both directions, electronically controllable.

**Head Mechanism:** Control of the Turnstile operation is achieved by an Electro-mechanical head mechanism and is silent in operation. It comprises:

- A positive action lock which prevents two passages at one time
- A self centring mechanism to ensure complete rotation of the head to the reset position.
- An anti backup device prevents reverse rotation once the head has moved 30° from its rest position.
- A hydraulic damper to ensure smooth and quiet operation

**Operating Modes:** The mechanism can be configured to operate in two standard modes.

- Normally Closed – The mechanism is locked until a valid authorisation signal is received.
- Normally Open – The mechanism is permanently unlocked and will only lock if passage is attempted without a valid authorised signal. In this mode the MTBF is increased from 1.5 to 2.5 million cycles and increases passage throughput speeds.

**Power Failure:** In the event of an emergency or isolation of power supply, unit may be configured to fail-safe i.e. rotor freely rotates or fail-lock i.e. rotor locks. Either option is available in both or one direction. Choice must be denoted at time of order placement.

Fire Alarm - Input facility available for voltage free contact supplied by others to effect fail safe.

Note: Head mechanism fail state will be the same as power failure choice.

**Interface:** The mechanism is controlled by means of an LCM02 microprocessor control logic with the following features:-

- One input for opening/locking the mechanism in each direction
- Two protected outputs for control of the opening/locking solenoids
- Four protected outputs for piloting way mode indicators.
- Two 0V output relays indicating availability of use in either direction.
- Two 0V outputs to count passage in either direction

The logic is protected against short circuits, overloads and polarity inversion. Additional detailed information is available upon request.

#### Product Description

ClearSec is an alternative approach to full height security from our Control range of products for internal or external use.

Choice of materials allows complete integration into any environment and 90 or a 120 degree rotor for easier entry.

#### Users include

- Government
- Retail
- Finance
- Telecommunications
- Information Technology
- Banking
- Publishing
- Leisure
- Petrochemical
- Pharmaceutical
- Education

**Control**



<b>Status Lights</b>	50mm diameter LED display Status Lights flush mounted within the ClearSec uprights. The Green badge symbol is continuously illuminated indicating passage is available. Upon authorisation a Green arrow will illuminate in the direction of passage authorisation whilst in the opposite direction a Red cross symbol will illuminate to indicate the unit is not available for use or is already in use.
<b>Walkway Lights:</b>	A 24 volt halogen walkway downlight is included as standard, which will be illuminated continuously  Unit has an adjustable time out facility if required i.e. Go signal will be cancelled if passage through turnstile is not completed within pre-set time. The standard default is 8 seconds adjustable via parameter change.
<b>Power Supply:</b>	115/230 Volts AC 5/60 Hz
<b>Power Rating:</b>	N/C – Standby or Passage 50Va (Alarm Condition 50Va) N/O – Standby or Passage 5Va (Alarm Condition 50 Va)
<b>Logic Voltage:</b>	24 Volt DC
<b>Installation Details:</b>	ClearSec GD models are delivered as a partly assembled kit of parts, which may require lifting gear for off loading.  Approx. weight 400 kg. Depending on spec.

## Models Available

### ClearSec GD – Internal/External Full Height Security Turnstile

- GD90 / GD120 Rotor - 316 stainless steel straight type arms and a black finished mild steel rotor column
- GD90SL / GD120 SL Rotor - 20mm thick acrylic slats with textured mid and bottom slats and black painted mild steel stator bars.
- GD90FP / GD120FP Rotor - Full length 9.5mm thick "Margard" polycarbonate panel rotor for internal use only

**Important Note:** *The Full length solid polycarbonate rotor panels should only be supplied as fail-safe to prevent trapping of pedestrians in the "dead" area during power failure. If fail lock is specified the written agreement of the customer to such a configuration must be obtained before the ClearSec GD is supplied by Gunnebo Entrance Control Ltd.*

### Accessories and Optional Extras

#### Alternative Materials and Finishes

- Casework finished with polyester powder coated semi-gloss paint
- Casework manufactured from 316 grade stainless steel EN10088-2 Grade IK/2K
- Tinted Glass
- Other Glazing types
- Grained Stainless Steel clad infill panels to replace standard glazed panels.
- Demountable roof fascia panels enabling access for reduced ceiling clearance of minimum 200mm.

#### Intermeshed (Refer to Gunnebo Entrance Control Ltd for details)

- In areas of restrictive space a reduced width double ClearSec GD can be supplied having intermeshed rotors.

#### Card Reader Mounting

- Readers can be surface mounted on casework upright
- Card Reader Mounting Pedestals.

#### Battery Back Up

- Maintains all 24 volts control facilities for 500 operations or 4 hours whichever the sooner.

#### Push Button Control

- Simple remote console to house ClearSec pushbutton overrides
- Remote console to specific requirements.
- Casework mounted pushbutton

#### Additional Interface

- RS 485 Serial Interface

## Installation Examples



**Flow Rates**

<b>Reader Device</b>	<b>Number per minute</b>
Insertion type	12
Insertion type with PIN code keypad	7.5
Swipe type	15
Swipe type with PIN code keypad	8.5
Proximity 'Hands Free'	17

- Please note the figures are approximate and must be confirmed with Gunnebo Entrance Control. Figures quoted are for one person per complete passage per walkway and per minute. It is assumed the access control authorisation response is instantaneous. Flow rates will increase with multiple passage use.

# **GUNNEBO**

## **ENTRANCE CONTROL**

### **United Kingdom**

Gunnebo Entrance Control Ltd. Bellbrook Business Park, Uckfield, East Sussex, TN22 1QQ.  
Tel +44 (0) 1825 761022 Fax +44 (0) 1825 763835

[www.gunneboentrance.com](http://www.gunneboentrance.com)

Note: In pursuit of its policy of continuous refinement and improvement, Gunnebo Entrance Control Ltd reserves the right to modify design and details.

### **A COMPANY WITHIN THE GUNNEBO GROUP .....**

#### **HEAD OFFICE SWEDEN**

Gunnebo Entrance Control AB, 590 93 Gunnebo, Tel +46 (0) 490 890 00, Fax +46 (0) 490 23889

**DENMARK** Gunnebo Protection A/S  
Division Entrance Control  
Erhvervsparken 3, DK-4621 Gadstrup  
Tel +45 46 19 14 66  
Fax +45 46 19 14 55

**FRANCE** Gunnebo Entrance Control SARL  
Zone d'Activites Le Mandinet,  
20 Rue des Campanules  
F-77185, Lognes  
Tel +33 (0) 1 64 80 14 40  
Fax +33 (0) 1 64 80 14 39

**GERMANY** Gunnebo Entrance Control GmbH  
Diagonalstrasse 41, D-20537  
Hamburg  
Tel +49 (0) 40 47 11 30 0  
Fax +49 (0) 40 47 11 30 79

**HONG KONG** Gunnebo Entrance Control  
Room 2312, C.C. Wu Building,  
302-308 Hennessy Road, Wanchai.  
Tel +852 2882 8337  
Fax +852 2523 7880

**ITALY** Gunnebo Entrance Control SpA  
Via A Volta 15 - IT 38015  
Lavis (TN)  
Tel +39 0461 248 900  
Fax +39 0461 248 999

**NORWAY** Gunnebo Troax A/S  
Division Entrance Control  
Postboks 179, Kalbakken N-0903, Oslo  
Tel +47 22 80 42 00  
Fax +47 22 80 42 01

**SPAIN** Gunnebo Entrance Control SL  
BBC, Comte d'Urgel 143, lola 08036,  
Barcelona  
Tel +34 93 452 59 56  
Fax +34 93 451 56 53

**SWEDEN** Gunnebo Entrance Control  
Box 500, Kumla Gardsvag 33F, 145 63  
Norsborg  
Tel +46 (0)8 53 17 15 75  
Fax +46 (0) 8 53 18 85 39

**UNITED KINGDOM** Gunnebo Entrance Control Ltd  
Bellbrook Business Park, Uckfield,  
East Sussex, TN22 1QQ  
Tel +44 (0) 1825 761022  
Fax +44 (0) 1825 763835

**USA** Gunnebo Omega Inc  
535 Getty Court, Suite F, Benicia  
California, CA 94510  
Tel +1 707 748 0885  
Fax +1 707 745 6020